




PLC PROLINE MARKING

MARKING

Photoluminescent marker paint. Universally applicable marking paint for roads, paths and terrains in the colors yellowgreen and lightblue, indoor and outdoor application, suitable for application on PLC Adhesive, free of solvents and plasticizers and environmentally friendly, excellent afterglow time and skid resistant according to legal standards.

APPLICATION	Concrete, asphalt, stone and all normally common surfaces.
PROCESSING	Well processable with spraying equipment, brush, roller on underlayer PLC Adhesive.
MATERIAL SETTING	Ready to use. Stir well. Dilutable up to 5% with water depending on the substrate.
COLOR	Yellowgreen and lightblue. Besides custom-made colors.
PACKAGING	5KG, 10KG, 20KG, >20KG
AVERAGE USAGE	0,59 KG/m ² with an average layer thickness of 225 micron
CLEANING TOOLS	Immediately after usage with water, optional with rinse aid for spraying equipment.
DRYING TIME	Paintable after approx. 90 minutes. Weather influences change the average drying.
STORAGE	In original packaging suitable for storage at +5 to +30dg. Celsius for approx. 9 months.
PERFORMANCE	Afterglow 5,3 cd/1min and 0,002 cd/9118min according to DIN-67510. These values are equal to a light perceivable to the human eye in the absolute darkness of 10 hours.
SKID RESISTANCE	R9 according to DIN-51130.
SPECIAL ATTENTION	Also consult the Technical Information and Safety Data Sheet, contact your dealer.



PLC PROLINE



Solar Powered Lighting Output