




# PLC PROLINE RENOVATOR

## RENOVATOR

Penetrative recovering primer. White pigmented, light filling, indoor and outdoor application, suitable for all common surfaces, free of solvents and plasticizers and environmentally friendly undercoat. Apply for recovering of critical substrates and extra adhesion on concrete and existing layers.

<b>APPLICATION</b>	Concrete, asphalt, stone, wood, metal, plastic and all normally common surfaces.
<b>PROCESSING</b>	Well processable with spraying equipment, brush, roller on carrying surfaces.
<b>MATERIAL SETTING</b>	Ready to use. Stir well. Dilutable up to 30% with water depending on the substrate.
<b>COLOR</b>	White
<b>PACKAGING</b>	5KG, 10KG, 20KG, >20KG
<b>AVERAGE USAGE</b>	0,18 KG/m <sup>2</sup> with an average layer thickness of 75 micron.
<b>CLEANING TOOLS</b>	Immediately after usage with water, optional with rinse aid for spraying equipment.
<b>DRYING TIME</b>	Paintable after approx. 30 minutes. Weather influences change the average drying.
<b>STORAGE</b>	In original packaging suitable for storage at +5 to +30dg. Celsius for approx. 9 months.
<b>SPECIAL ATTENTION</b>	Also consult the Technical Information and Safety Data Sheet, contact your dealer.



**PLC PROLINE**



Solar Powered Lighting Output