


PLC PROLINE ADHESIVE

ADHESIVE

Extreme adhesive primer. Super-tight formula, uni colors in white yellow and blue, indoor and outdoor application, suitable for all common surfaces, free of solvents and plasticizers and environmentally friendly. Special underlayer for PLC Road, PLC Marking, PLC Systemcoat and PLC Safety.

APPLICATION	Concrete, asphalt, stone, wood, metal, plastic and all normally common surfaces.
PROCESSING	Well processable with spraying equipment, brush, roller on carrying surfaces.
MATERIAL SETTING	Ready to use. Stir well. Dilutable up to 10% with water depending on the substrate.
COLOR	White, yellow and blue
PACKAGING	5KG, 10KG, 20KG, >20KG
AVERAGE USAGE	0,26 KG/m ² with an average layer thickness of 150 micron.
CLEANING TOOLS	Immediately after usage with water, optional with rinse aid for spraying equipment.
DRYING TIME	Paintable after approx. 60 minutes. Weather influences change the average drying.
STORAGE	In original packaging suitable for storage at +5 to +30dg. Celsius for approx. 9 months.
SPECIAL ATTENTION	Also consult the Technical Information and Safety Data Sheet, contact your dealer.



PLC PROLINE



Solar Powered Lighting Output