




# PLC PROLINE AEGIS

## AEGIS

Wear-resistant dirt-repellent coating. Universally applicable transparent thin liquid paint to be applied as the top layer, indoor and outdoor application, suitable for application on PLC Marking/PLC Road/PLC Systemcoat and PLC Safety, extra wear resistance and dirt repellent for longer lifetime.

<b>APPLICATION</b>	All normally common surfaces.
<b>PROCESSING</b>	Well processable with spraying equipment, brush, roller on carrying surfaces.
<b>MATERIAL SETTING</b>	Ready to use. Stir well.
<b>COLOR</b>	Clear transparent
<b>PACKAGING</b>	5KG, 10KG, 20KG, >20KG
<b>AVERAGE USAGE</b>	0,09 KG/m <sup>2</sup> with an average layer thickness of 60 micron.
<b>CLEANING TOOLS</b>	Immediately after usage with water, optional with rinse aid for spraying equipment.
<b>DRYING TIME</b>	Paintable after approx. 15 minutes. Weather influences change the average drying.
<b>STORAGE</b>	In original packaging suitable for storage at +5 to +30dg. Celsius for approx. 9 months.
<b>SPECIAL ATTENTION</b>	Also consult the Technical Information and Safety Data Sheet, contact your dealer.



PLC PROLINE



Solar Powered Lighting Output